



The Jisc Assent Service Portal

How to use it


The Portal

How to use it

- » The portal controls your organisation's settings in the Trust Router network
- » It is fairly easy to use

Default view

This is what you see by default



You are logged in as <https://idp.company.ja.net/idp/shibboleth!https://portal.moonshot.ja.net/shibboleth!62boJbTarkELqrZCYyOyVI>

© Painless Security 2012, 2013

Organisation view

This is what you see by default

Jisc Assent Welcome Communities Organisation Admin Help

Organisations

10 records per page

Search:

Name ▲	Service provider realms	ID provider realms	Status ▼		
Camford University	<ul style="list-style-type: none">cs.camford.ac.ukit.camford.ac.uk	<ul style="list-style-type: none">cs.camford.ac.uk -camford.ac.uk -maths.camford.ac.uk -	Inactive	Edit	

Showing 1 to 1 of 1 entries

← Previous 1 Next →

Organisation view

Your organisation

Camford University

General Service Realms ID Provider Realms Credential Admins Moderated Edits

Name Camford University

Description

This organisation is currently inactive. Please contact the systems administrators to activate it again.

Realms

Service Realms

Name	Realm	
Computer Science	cs.camford.ac.uk	
Central IT	it.camford.ac.uk	
		

ID Provider Realms

Name	Edit
Camford CS	
Camford University	
Camford Maths	
	

[Update Organization](#)

[Cancel](#)

Organisation view

How to use it

» Service Realms

- › Your services/service groups at your organisation

» ID Provider Realms

- › Identity realms provided by your organisation

» Credential, Admins, Moderated Edits

- › Download your Trust Router credential here
- › Add and delete management contacts here
- › See an audit log of changes (pending/rejected)

Service Realms view

Camford University

General Service Realms ID Provider Realms Credential Admins Moderated Edits

Computer Science

Central IT

+ New Service Realm

Name

Central IT

Realm

it.camford.ac.uk

Delete

Enabled

Enabled

Disabled

Constraints

The system will constrain which domain names are allowed to claim membership in this service realm. By default, the constraints permit no domains. Add a set of domains that will be allowed as members in this service realm.

Domain Constraints

Domains Allowed

it.camford.ac.uk



*.it.camford.ac.uk



Update Organization

Cancel

Service Realms view

How to use it

- » Name: Description of your group of services
- » Realm: This is identical to 'rp_realm' in 'mods-available/realm' module in FreeRADIUS configuration
- » Domain Constraints: The 'gss_acceptor_host_name' setting in 'sites-available/abfab-tls' clients section has to match these constraints. Can use a wildcard (easier).
- » You can enable/disable realms
- » Each service realm needs its own RP Proxy

ID Provider Realms view

Camford University

General Service Realms ID Provider Realms Credential Admins Moderated Edits

Camford CS

Camford University

Camford Maths

➕ New Identity Realm

Name

Camford CS

Realm

cs.camford.ac.uk

Delete

Enabled

Enabled

Disabled

Temporary logins

Share across IdP servers

Create per IdP server

AAA Servers

AAA Server

cs.camford.ac.uk

IP Addresses

• 212.219.210.203



Update Organization

Cancel

ID Provider Realms view

How to use it

- » Name: Description of your ID realm
 - › Can just be your realm name too
- » Realm: This is what's to the right of the @-sign
- » AAA Server: The server that will handle this realm
 - › This is your actual Moonshot IdP server!
- » You can enable/disable the realms too

Credential view

Camford University

[General](#)[Service Realms](#)[ID Provider Realms](#)[Credential](#)[Admins](#)[Moderated Edits](#)

Generate and download new credential

Generate a new credential to use across all of this organization's AAA servers. Generating a new credential will prevent all existing AAA servers from working within the trust framework until the servers are updated with the new credential.

Generate and Download New Credential 

Update Organization

Cancel

Credential view

How to use it

- » Click the button to download the credential!
- » Only one credential needed per organisation
- » The XML file is imported with moonshot-webp to the radiusd/freerad and trustrouter users
- » You will get a new credential every time you click
 - › This is for security – Makes credential compromises difficult
- » Management contacts should share the file amongst themselves (remember security!)

Admins view

Camford University

[General](#)[Service Realms](#)[ID Provider Realms](#)[Credential](#)[Admins](#)[Moderated Edits](#)

Current administrators

The following people administer Camford University:

- stefan.paetow@ja.net (You)

Open invitations

The following people have pending invitations to administer Camford University:

Invite administrators

Invite the following people to administer Camford University (fictional):

Email Addresses

[Update Organization](#)[Cancel](#)

Admins view

How to use it

- » Jisc will add your management contacts in the application form for you
- » You can invite others:
 - › Add email address of contact, hit Enter
- » Invited users listed on the right
 - › Expired invites are listed as scratched out
- » Click on the (x) to delete a contact
- » Management contact logins associated with invite after first logon with UKAMF.

Moderated Edits view

Camford University

General Service Realms ID Provider Realms Credential Admins **Moderated Edits**

Pending Edits

Change type	Value	Date requested
Constraint	cs.camford.ac.uk	April 02, 2015 11:41

Rejected Edits

10 records per page

Proposed change	Refusal reason	Date refused
-----------------	----------------	--------------

No data available in table

Showing 0 to 0 of 0 entries

← Previous Next →

Moderated Edits view

How to use it

- » Lists pending edits, rejected edits with reasons why
- » It's an audit log for you
- » Actions that need approval from Jisc:
 - › Adding ID or service realms
 - › Adding domain constraints
- » Why??
 - › This is a trust network, we can't have someone claiming to be Google.com unless it's actually Google!

Communities view

Edit

Name

Community medresearch.communities.moonshot.ja.net

Description

Associations

Authentication policy communities

Core APC

Identity realms

diamond.ac.uk(diamond.ac.uk)

stfc.ac.uk(stfc.ac.uk)

Service realms

moonshot-
rp.esc.rl.ac.uk(moonshot-
rp.esc.rl.ac.uk)

diamond.ac.uk(diamond.ac.uk)

Communities view

How to use it

- » Give community a name
(camford.communities.moonshot...)
- » Choose an APC you're part of
- » Choose IdPs and Services (here human-readable names are useful)
- » Communities don't need Jisc approval

Communities view

How to use it

- » RP Proxies are always part of the default APC community
- » Default APC community is in 'mods-available/realm' 'default_community' setting in FreeRADIUS
- » Jisc will tell you what your default APC community is
- » Your services themselves can be part of different communities, set in 'sites-available/abfab-tls' client section, 'trust_router_coi' setting (set to same as 'default_community' until different one needed).